

OUTAGE TABLE

JOB NO. 3060-TS SER. NO. 161593-01-54 R. T. C. NO. 54 **6622**

1 FEET		2 FEET		3 FEET		4 FEET		5 FEET		6 FEET		7 FEET	
IN.		IN.		IN.		IN.		IN.		IN.		IN.	
0		0	22,453	0	20,125	0	17,216	0	13,987	0	10,621	0	7,338
1/4		1/4	22,412	1/4	20,069	1/4	17,151	1/4	13,918	1/4	10,551	1/4	7,272
1/2		1/2	22,371	1/2	20,013	1/2	17,086	1/2	13,849	1/2	10,482	1/2	7,206
3/4		3/4	22,331	3/4	19,957	3/4	17,022	3/4	13,780	3/4	10,412	3/4	7,140
1	23,635	1	22,290	1	19,901	1	16,957	1	13,711	1	10,343	1	7,074
1/4	23,627	1/4	22,247	1/4	19,844	1/4	16,891	1/4	13,641	1/4	10,274	1/4	7,008
1/2	23,619	1/2	22,205	1/2	19,787	1/2	16,825	1/2	13,571	1/2	10,204	1/2	6,942
3/4	23,611	3/4	22,163	3/4	19,730	3/4	16,759	3/4	13,501	3/4	10,134	3/4	6,876
2	23,603	2	22,120	2	19,673	2	16,693	2	13,431	2	10,065	2	6,810
1/4	23,588	1/4	22,076	1/4	19,614	1/4	16,627	1/4	13,362	1/4	9,995	1/4	6,745
1/2	23,573	1/2	22,032	1/2	19,556	1/2	16,562	1/2	13,292	1/2	9,925	1/2	6,679
3/4	23,558	3/4	21,988	3/4	19,498	3/4	16,496	3/4	13,223	3/4	9,856	3/4	6,614
3	23,543	3	21,944	3	19,440	3	16,430	3	13,154	3	9,787	3	6,549
1/4	23,524	1/4	21,898	1/4	19,381	1/4	16,364	1/4	13,084	1/4	9,718	1/4	6,484
1/2	23,505	1/2	21,853	1/2	19,322	1/2	16,297	1/2	13,015	1/2	9,648	1/2	6,419
3/4	23,485	3/4	21,808	3/4	19,264	3/4	16,231	3/4	12,945	3/4	9,580	3/4	6,355
4	23,466	4	21,762	4	19,205	4	16,165	4	12,876	4	9,511	4	6,291
1/4	23,444	1/4	21,715	1/4	19,145	1/4	16,098	1/4	12,806	1/4	9,442	1/4	6,226
1/2	23,422	1/2	21,668	1/2	19,086	1/2	16,031	1/2	12,737	1/2	9,373	1/2	6,162
3/4	23,399	3/4	21,622	3/4	19,026	3/4	15,964	3/4	12,667	3/4	9,304	3/4	6,098
5	23,377	5	21,575	5	18,967	5	15,898	5	12,597	5	9,236	5	6,035
1/4	23,352	1/4	21,527	1/4	18,906	1/4	15,830	1/4	12,527	1/4	9,167	1/4	5,971
1/2	23,326	1/2	21,479	1/2	18,845	1/2	15,762	1/2	12,457	1/2	9,099	1/2	5,907
3/4	23,301	3/4	21,430	3/4	18,785	3/4	15,695	3/4	12,386	3/4	9,030	3/4	5,844
6	23,276	6	21,382	6	18,724	6	15,627	6	12,316	6	8,960	6	5,780
1/4	23,247	1/4	21,333	1/4	18,663	1/4	15,559	1/4	12,245	1/4	8,891	1/4	5,716
1/2	23,219	1/2	21,283	1/2	18,602	1/2	15,492	1/2	12,175	1/2	8,822	1/2	5,653
3/4	23,191	3/4	21,233	3/4	18,541	3/4	15,425	3/4	12,104	3/4	8,754	3/4	5,590
7	23,162	7	21,184	7	18,480	7	15,357	7	12,033	7	8,686	7	5,528
1/4	23,131	1/4	21,133	1/4	18,418	1/4	15,289	1/4	11,961	1/4	8,618	1/4	5,465
1/2	23,099	1/2	21,082	1/2	18,356	1/2	15,221	1/2	11,890	1/2	8,550	1/2	5,403
3/4	23,067	3/4	21,032	3/4	18,294	3/4	15,153	3/4	11,818	3/4	8,482	3/4	5,341
8	23,035	8	20,981	8	18,233	8	15,086	8	11,746	8	8,414	8	5,279
1/4	23,001	1/4	20,929	1/4	18,170	1/4	15,017	1/4	11,674	1/4	8,346	1/4	5,218
1/2	22,967	1/2	20,877	1/2	18,108	1/2	14,949	1/2	11,602	1/2	8,278	1/2	5,156
3/4	22,934	3/4	20,825	3/4	18,045	3/4	14,881	3/4	11,531	3/4	8,211	3/4	5,095
9	22,900	9	20,774	9	17,983	9	14,813	9	11,461	9	8,143	9	5,034
1/4	22,865	1/4	20,721	1/4	17,919	1/4	14,744	1/4	11,390	1/4	8,076	1/4	4,973
1/2	22,829	1/2	20,668	1/2	17,856	1/2	14,675	1/2	11,319	1/2	8,009	1/2	4,912
3/4	22,794	3/4	20,615	3/4	17,792	3/4	14,606	3/4	11,249	3/4	7,941	3/4	4,851
10	22,759	10	20,562	10	17,728	10	14,537	10	11,179	10	7,873	10	4,790
1/4	22,721	1/4	20,508	1/4	17,665	1/4	14,468	1/4	11,108	1/4	7,805	1/4	4,729
1/2	22,684	1/2	20,453	1/2	17,601	1/2	14,400	1/2	11,038	1/2	7,738	1/2	4,669
3/4	22,647	3/4	20,399	3/4	17,537	3/4	14,331	3/4	10,969	3/4	7,671	3/4	4,609
11	22,609	11	20,345	11	17,473	11	14,262	11	10,899	11	7,604	11	4,550
1/4	22,570	1/4	20,290	1/4	17,409	1/4	14,194	1/4	10,829	1/4	7,538	1/4	4,490
1/2	22,531	1/2	20,235	1/2	17,345	1/2	14,125	1/2	10,760	1/2	7,471	1/2	4,431
3/4	22,492	3/4	20,180	3/4	17,281	3/4	14,056	3/4	10,690	3/4	7,405	3/4	4,372

CAPACITY IN: U. S. GALLONS TAPE CALIBRATED: 2/8/80

2% OUTAGE = 23,162 GALLONS (1'-7" FROM RIM OF HATCH)

SHELL FULL = 23,635 GALLONS (9'-1 1/2" INNAGE OR

1'-1" OUTAGE)

GAUGE HEIGHT: 10'-2 1/2" (FROM RIM OF HATCH)

by *J. L. Lawton*

OUTAGE TABLE

JOB NO. 3060-TS

SER. NO. 161593-01-54

R. T. C. NO. 54

8 FEET		9 FEET		10 FEET		FEET		FEET		FEET		FEET	
IN.		IN.		IN.		IN.		IN.		IN.		IN.	
0	4,313	0	1,783	0	131	0		0		0		0	
1/4	4,254	1/4	1,737	1/4	112	1/4		1/4		1/4		1/4	
1/2	4,196	1/2	1,692	1/2	92	1/2		1/2		1/2		1/2	
3/4	4,137	3/4	1,648	3/4	78	3/4		3/4		3/4		3/4	
1	4,079	1	1,603	1	63	1		1		1		1	
1/4	4,021	1/4	1,559	1/4	48	1/4		1/4		1/4		1/4	
1/2	3,963	1/2	1,515	1/2	33	1/2		1/2		1/2		1/2	
3/4	3,906	3/4	1,473	3/4	25	3/4		3/4		3/4		3/4	
2	3,849	2	1,430	2	16	2		2		2		2	
1/4	3,792	1/4	1,388	1/4	8	1/4		1/4		1/4		1/4	
1/2	3,735	1/2	1,346	1/2	0	1/2		1/2		1/2		1/2	
3/4	3,679	3/4	1,305	3/4		3/4		3/4		3/4		3/4	
3	3,623	3	1,264	3		3		3		3		3	
1/4	3,567	1/4	1,223	1/4		1/4		1/4		1/4		1/4	
1/2	3,511	1/2	1,183	1/2		1/2		1/2		1/2		1/2	
3/4	3,456	3/4	1,143	3/4		3/4		3/4		3/4		3/4	
4	3,401	4	1,104	4		4		4		4		4	
1/4	3,346	1/4	1,065	1/4		1/4		1/4		1/4		1/4	
1/2	3,291	1/2	1,026	1/2		1/2		1/2		1/2		1/2	
3/4	3,237	3/4	989	3/4		3/4		3/4		3/4		3/4	
5	3,182	5	952	5		5		5		5		5	
1/4	3,128	1/4	914	1/4		1/4		1/4		1/4		1/4	
1/2	3,074	1/2	877	1/2		1/2		1/2		1/2		1/2	
3/4	3,021	3/4	842	3/4		3/4		3/4		3/4		3/4	
6	2,968	6	806	6		6		6		6		6	
1/4	2,915	1/4	771	1/4		1/4		1/4		1/4		1/4	
1/2	2,862	1/2	736	1/2		1/2		1/2		1/2		1/2	
3/4	2,810	3/4	702	3/4		3/4		3/4		3/4		3/4	
7	2,758	7	668	7		7		7		7		7	
1/4	2,706	1/4	634	1/4		1/4		1/4		1/4		1/4	
1/2	2,654	1/2	600	1/2		1/2		1/2		1/2		1/2	
3/4	2,604	3/4	569	3/4		3/4		3/4		3/4		3/4	
8	2,553	8	537	8		8		8		8		8	
1/4	2,503	1/4	505	1/4		1/4		1/4		1/4		1/4	
1/2	2,452	1/2	473	1/2		1/2		1/2		1/2		1/2	
3/4	2,402	3/4	445	3/4		3/4		3/4		3/4		3/4	
9	2,353	9	416	9		9		9		9		9	
1/4	2,303	1/4	388	1/4		1/4		1/4		1/4		1/4	
1/2	2,253	1/2	360	1/2		1/2		1/2		1/2		1/2	
3/4	2,205	3/4	334	3/4		3/4		3/4		3/4		3/4	
10	2,157	10	309	10		10		10		10		10	
1/4	2,109	1/4	284	1/4		1/4		1/4		1/4		1/4	
1/2	2,061	1/2	259	1/2		1/2		1/2		1/2		1/2	
3/4	2,014	3/4	236	3/4		3/4		3/4		3/4		3/4	
11	1,967	11	214	11		11		11		11		11	
1/4	1,920	1/4	192	1/4		1/4		1/4		1/4		1/4	
1/2	1,873	1/2	169	1/2		1/2		1/2		1/2		1/2	
3/4	1,828	3/4	150	3/4		3/4		3/4		3/4		3/4	

CAPACITY IN: U. S. GALLONS

TAPE CALIBRATED: 2/8/80

GAUGE HEIGHT: 10'-2 1/2" (FROM RIM OF HATCH)

BY *J. L. Ramton*